

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB2006/000903

International filing date: 13 March 2006 (13.03.2006)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0505004.2
Filing date: 11 March 2005 (11.03.2005)

Date of receipt at the International Bureau: 10 April 2006 (10.04.2006)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT/GB 2006 / 0 0 0 9 0 3

3

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

He Behen

Dated 22 March 2006

Patents Form 1/77

Patents Act 1977
(Rule 16)



1 MAR 05 15:15 1 DC2813
FOI 7777 30.00-0505004.2 CH
1777

Request for grant of a patent

(An explanatory leaflet on how to fill in this form is available from the Patent Office)

Application Number GB

THE PATENT OFFICE

C

11 MAR 2005

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your Reference
(optional)

NEWPORT
P5151TU GB

0505004.2

2. Full name, address and postcode of the applicant
or of each applicant (*underline all surnames*)

Dubois Limited
Amaray House
Arkwright Road
Corby
Northants
NN17 5AE

11 MAR 2005

Patents ADP number (*if you know it*)

7269467002

If the applicant is a corporate body, give the country/state of its incorporation

England & Wales

3. Title of the invention

Injection Moulded Container

4. Name of you agent (*if you have one*)

Fry, Heath & Spence LLP

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

The Gables
Massetts Road, Horley
Surrey RH6 7DQ

Patents ADP number (*if you know it*)

08459554001

5. Priority declaration: Are you claiming priority from one or more earlier-filed patent applications? If so, please give details of the application(s):

Country

Application number
(*if you know it*)

Date of filing
(*day / month / year*)

6. Divisionals, etc: Is this application a divisional application, or being made following resolution of an entitlement dispute about an earlier application? If so, please give the application number and filing-date of the earlier application:

Number of earlier UK application

Date of filing
(*day / month / year*)

7. Inventorship: (Inventors must be individuals not companies)

(Please tick the appropriate boxes)

Are all the applicants named above also inventors?

YES

NO ☒

If yes, are there any other inventors?

YES

NO

8. Are you paying the application fee with this form?

YES ☒

NO

Patents Form 1/77

9. Accompanying documents: not counting duplicates, please enter the number of pages of each item accompanying this form:

Continuation sheets of this form	0
Description	9
Claims(s)	4
Abstract	0
Drawing(s)	5

Country

Application Number

Date of filing
(day/month/year)


If you are not filing a description, please give details of the previous application you are going to rely upon:

10. If you are also filing any of the following, state how many against each item.

Priority documents	0
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	0
Request for search (Patents Form 9A/77)	1
Request for substantive examination (Patents Form 10/77)	0
Any other documents (please specify)	0

11. I/We request grant of a patent on the basis of this application.

Signature(s)



Date
10 March 2005

12. Name, email address, telephone, Fax and/or mobile number, if any, of a contact point for the applicant

S. G. Unwin
01865 841060

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you are resident in the United Kingdom and your application contains information which relates to military technology, or would be prejudicial to national security or the safety of the public, section 23 of the Patents Act 1977 prohibits you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

A leaflet on how to fill in this form is available from the Patent Office. If you would like a copy of the leaflet it is available on our website at <http://www.patent.gov.uk/patent/info/fact05.pdf> or alternatively you could telephone 08459 500505 or send an email to enquiries@patent.gov.uk to request a copy

INJECTION MOULDED CONTAINER

This invention relates to a method of making an injection moulded container for housing information storage media, to containers made by the method and to mould tools for use in said method.

Containers comprising a base portion and a lid portion moveable about a spine portion between an open and a closed configuration and having holding means for holding information storage media within the container are well known. One widely used container of this type is a container for housing DVDs.

The industry has adopted DVD containers having substantially uniform external dimensions so they are readily recognised by the consumer as containing a DVD (rather than, for instance, a music CD) and so they are compatible with both display systems used in retail outlets and storage devices used by the consumer.

The moulds used for making such injection moulded containers are made to a very high specification so as to be able to reliably fabricate hundreds of thousands, or millions, of containers to the desired quality. Fabrication of such tools is thus very expensive and can take a considerable length of time (typically several months).

For the above reasons, the containers produced by a given manufacturer tend to be relatively standardized. However, the studios providing the content of a DVD, e.g. particular software or a particular movie or film, also have a desire for their products to be readily identifiable and distinguishable when presented to the consumer, e.g. in a retail outlet. The present invention aims to provide a technical solution to these conflicting requirements.

According to a first aspect of the invention, there is provided a method of making an injection moulded container for housing information storage media, the container comprising a base portion and a lid portion moveable about a spine portion between an open and a closed configuration and holding means for holding the information storage media within the container, the method involving the use of an injection moulding tool comprising two carrier units each of which is adapted to receive a plurality of inserts therein which together define

a cavity for forming the container: a first set of the inserts for forming a first set of features of the container being formed of a first material and a second set of inserts for forming a second set of features of the container being formed of a second material, the first set of inserts being machined to the required shape for fitting within the carrier units and for forming the first set of features and the second set of inserts being machined so as to fit within the carrier units but one or more of the second set of inserts being formed with excess material on surfaces thereof defining said second set of features pending a decision as to the precise shape of said second set of features, whereby once said decision has been made the tool can be completed by machining said excess material to the required shape and assembling the inserts in the mould.

The invention also relates to containers made by this method. In addition, the invention provides a plurality of such injection moulded containers each being similar apart from some having a first set of customer specific features and some having a second set of customer specific features (differing from the first set).

The invention also relates to a mould tool for use in the above method and, in particular, to a mould tool comprising a first set of inserts for forming a first set of features and a plurality of second sets of inserts each second set being for forming a different set of customer specific features.

Preferred and optional features will be apparent from the following description and from the subsidiary claims of the specification.

The invention will now be further described, merely by way of example, with reference to the accompanying drawings, in which:

Figure 1A is a perspective view of the exterior of a DVD container according to a first embodiment of the invention (shown closed) and Figure 1B is a perspective view of the interior of the container (shown in an open position);

Figure 2 is a perspective view of the interior of the DVD container of Figure 1 (shown in an open position);

Figure 3A is a perspective view of the exterior of a DVD container according to a second embodiment of the invention (shown closed) and Figure 3B is a perspective view of the interior of the container of Figure 3A (shown in an open position);

Figure 4 is a further perspective view from a different angle of the interior of the container shown in Figures 3A and 3B (in an open position); and

Figure 5 is a schematic, plan view of components used in making up an injection moulding tool according to a preferred form of the invention.

Figure 1 shows a first embodiment of a DVD container according to the present invention comprising a base portion 10 connected to a lid portion 11 by a spine portion 12. This is similar to a known DVD container except that a clear plastic film attached to the exterior of the container and cover sheet 13 (shown blank in Figure 1) positioned behind the film does not cover the entire front face of the container but, instead, leaves a band 14 at the top where the outer surface of the container remains exposed. The band 14 extends across the front face of the container, around the spine and across the rear face of the container. This band 14 is available for customized moulding, e.g. of graphics or logos. In the example shown, a series of words (represented by lines 14A) are moulded in the area of the band 14 on the front face of the container. These may, for example, be the name of the studio, movie or artist. Alternatively, or additionally, logos or other symbols of a more 3-dimensional nature may be moulded in the area of the band 14, e.g. projecting therefrom by up to 3mm. Alternatively or additionally, the surfaces of the container in the area of the band 14 may be customized so as to have a distinctive shape or appearance, e.g. the edges, corners and/or faces thereof may be formed with various convex, concave or angular features (but not the external surfaces formed by steel inserts 50, 51, 52, 53 – see below). Preferably, this band around the upper end of the container stands proud, e.g. by 0.5-1.0mm, of the adjacent surfaces of the container.

A similar band which is not covered by a film and cover sheet 13 may be provided around the lower end of the container (either in place of the band at the upper end or in addition thereto).

In a further arrangement, the film and cover sheet 13 may be omitted so the major faces of the lid, spine and base portions may be provided with customised features at any position thereon.

Figure 1B and Figure 2 show the interior of the container. A hub 15 is provided on the interior of the base portion 10 for receiving a DVD (or HD DVD) and a circular upstand 16 is provided for surrounding the periphery of the DVD. In the embodiment shown, the upstand 16 is positioned substantially centrally in the base portion 10 so spaces 17A and 17B are left at either end of the base portion. Internal graphics features may be formed in the spaces 17A and 17B (as represented by the blanked out areas in the Figures). Graphics, or other customised features can, however, be formed anywhere on the internal faces of the base, spine and lid portions (apart from those areas which are formed by steel inserts, e.g. inserts 54, 56, 57 - see below). The illustrated embodiment shows a star shape 18 moulded on the base portion within the area defined by the circular upstand 16 and extending beyond this (together with customised V-shaped grooves formed within the upstand 16). It is known to mould graphics features in areas such as spaces 17A and 17B but the present invention enables this to be done in a manner which enables the mould tool used to form the container to be easily and rapidly modified or customized to provide specific features in these areas. Instead of having to make a new tool or modify an existing tool by re-machining parts thereof to provide specific features, the desired features can be provided by substituting one set of inserts for another set of inserts. Moreover, the present invention enables this to be done within a shorter time frame than has previously been possible. By pre-forming inserts for the tool so they are ready to be inserted therein but leaving excess material on the surfaces thereof defining areas in which customisable features can be formed, the tool can be completed merely by machining said excess material to the required shape and assembling the inserts into the mould.

In a preferred embodiment, the inserts used to form the customisable features are formed of a relatively soft material, e.g. a copper alloy, so they can be easily and rapidly machined to the required shape. In contrast, other features of the container are typically formed by inserts formed of a steel alloy. Machining of steel inserts typically requires the insert to be machined to the approximate shape required, then heat-treated to harden the steel. The material tends to warp during heat treatment so then goes through a second machining process to form the final shape. As indicated above, it can typically take several months to fabricate steel mould components in this manner. In contrast, copper based alloys (e.g. moldMAX® made by Brush Wellman Inc) can be machined relatively easily and in one-stage and so can typically be fabricated in a few weeks rather than a few months. This is particularly so in moulding apparatus having more than one mould cavity, e.g. a 4-cavity machine having 4 identical cavities which are used simultaneously in each mould cycle.

In a preferred method according to the present invention, once machining of the copper alloy inserts is complete, they are provided with a hard coating, e.g. of a nickel or titanium alloy, at least over surfaces thereof which define the shape of a part of the container, preferably with an additional outer coating of chromium to provide resistance to tarnishing.

The method thus enables the container manufacturer to rapidly modify the injection moulding tool to provide customized features, e.g. for DVDs relating to a specific film or movie. The ability to modify the tool within a few weeks enables this to be achieved whereas, in many cases, if the tool modification takes months, the needs of this market are difficult to meet.

Figures 3A, 3B and 4 show another embodiment of a DVD container having specific customized features. As for the embodiment described above, the exterior of the case has an area 30 in which a conventional display is provided by a printed sheet positioned behind a clear film attached to the exterior of the container and a second area 31 in the form of a band, adjacent the upper end of the container, where the external surface of the injection moulded container is exposed and where customised features can be formed.

In the interior of the container, customised features are formed in the flat areas 32A and 32B on the exposed surfaces of the interior of the base portion outside an upstand 33. A logo may, for example, be moulded in area 32A and the name of a film or series to which the DVD to be housed in the container relates may be moulded in area 32B. In addition, as best shown in Figure 4, the shape of the upstand 33 may be customized, e.g. to tie in with a feature of the logo or movie. In the example shown, the upstand has a substantially circular inner edge but comprises two portions of tapering width spaced 180° from each other. It will be appreciated that the upstand can be formed in a wide variety of other shapes and forms with little or no effect on its function. Preferably, the inner edge of the upstand is circular, or partially circular, but away from this inner edge both its shape and gaps within it can vary considerably.

Preferably, the customisable inserts form static features of the container, i.e. features which are fixed relative to the base portion, spine portion or lid portion. Other features, which need to be formed with a very high degree of accuracy and/or the shape of which requires more complex moulding techniques, are preferably made with steel inserts or components. Such features are thus likely to be the same in all customised containers formed by a method in accordance with the present invention.

The static features may typically comprise:

- (i) specific external features of the box, e.g. the shape of the exposed upper end of the box and/or features moulded in the band described above.
- (ii) internal graphics features, e.g. names, logos or trade marks, moulded in the major internal surface of the base portion,
- (iii) the shape of an upstand surrounding the periphery of the DVD.

Figure 5 shows a plan view of components of an embodiment of a mould tool according to the present invention. The tool comprises two carrier units 40, 41 to which the various mould inserts are assembled (e.g. by being bolted or

screwed thereto). The carrier units 40, 41 are in turn fastened to the bolsters of a moulding machine. The provision of carrier units 40, 41 enables the configuration of inserts used in the mould to be easily and rapidly changed.

Two sets of inserts are provided for attachment to the carrier units 40, 41: a first set defining a first set of features, and a second set defining a second set of features. As described above, the first set of inserts is made from a first material, e.g. a steel, and the second set of inserts is made from a second material, e.g. a copper alloy.

In the example shown, the second set of inserts comprises: an exterior inset 42 for forming some of features of the major external faces of the container, an interior lid insert 43 for forming the interior of the lid portion, an interior spine

insert 44 for forming the interior of the spine portion, and an interior base portion 45 for forming some of the features of the interior of the base portion.

The first set of inserts includes: exterior edge inserts 50, 51, 52, 53 for forming the external surfaces of the edges of the container, internal and external hub inserts 54, 55 for forming the internal and external features of a disk holding hub, booklet clip inserts 56, 57 for forming external surfaces of resilient booklet clips (typically provided in the lid portion of DVD boxes to hold a booklet or other documents), and opening edge inserts 58, 59 for forming features of the opening edge of the container.

The first set of inserts may include a variety of other members but these are not shown in order to simplify the description.

It will be appreciated that the members of the first and second sets of insert fit together within the carrier units 40, 41 to form the two sides of a mould cavity for defining the shape of the container to be formed therein. In some cases, the members fit adjacent each other, in other cases one member fits within another (it will be seen from Figure 5, for example, that the hub inserts 55 and booklet clip inserts 56, 57 fit within corresponding apertures of the exterior insert 42).

A further possibility is to replace one or more of the steel inserts by a further insert. This further insert may be formed of steel, e.g. if it takes the form of a

blank when, for example, it is desired to make a container without booklet clips in the lid portion, or when it is desired to provide a limited number of options in the standard features of the container, for example it is desired to provide the option of two forms of hub (such as a 2-arm hub or a 3-arm hub). In other cases, if customised features are required, one or more of the steel inserts may be replaced by a customised inset of a softer material.

The mould is preferably designed so that the majority of clamping forms used to clamp the two halves of the mould together are borne by the insert carriers 40, 41 and/or by steel inserts rather than the second set of insets which are made of a relatively soft material. For this reason, it is desirable for the edge inserts 50, 51, 52 and 53 which form the periphery of the mould cavity, to be formed of steel. It is also possible to replace steel inserts such as edge inserts 50, 51, 52 and 53 with customised steel inserts. However, whilst manufacture and replacement of steel inserts will be quicker than fabricating an entirely new steel mould, such steel inserts take longer to manufacture than inserts of a softer material so this would lead to a partial loss of the time advantages discussed above.

A further advantage of the above arrangement of inserts is that if the second set of inserts are formed of a material having a relatively high thermal conductivity (such as a copper alloy), this assists in cooling the mould after the injection of plastics material therein and so assists in shortening the cycle time of each mould cycle.

As explained above, the container manufacturer is able to pre-prepare moulds for making customized containers. All the first set of mould inserts can be completed. As these form features which are common to all containers to be formed in the mould they can be made in advance of an anticipated need for a customised container. The second set of mould insets are also part-machined so they fit in the mould and are ready for use apart from final machining of the excess material left on the surfaces where customised features may be required. The container manufacturer will thus have for each mould, a first set of mould inserts for the common features and a plurality of sets of second mould inserts

some sets including the excess material (ready for machining to a customised shape) and other sets in which a customised shape has been machined but which have been removed from the mould whilst a different second set of inserts are in use. As the inserts are readily removable, a mould can be set up for a specific mould run, e.g. of a hundred thousand containers, and once this has been completed, the second set of inserts can be changed for a different set ready for fabricating another container with a different set of customised features.

Because of the relative ease with which the second set of inserts can be manufactured and the relative ease of re-configuring the mould tool, the arrangement described above enables the container manufacturer to be much more adaptable and to be able to respond to specific container requirements at relatively short notice and at relatively little additional expense. The arrangement also enables a relatively short run, e.g. of one hundred thousand containers, of a specific, customised form of container to be economic (rather than requiring a run of several hundreds of thousands or millions of containers to achieve this).

CLAIMS

1. A method of making an injection moulded container for housing information storage media, the container comprising a base portion and a lid portion moveable about a spine portion between an open and a closed configuration and holding means for holding the information storage media within the container, the method involving the use of an injection moulding tool comprising two carrier units each of which is adapted to receive a plurality of inserts therein which together define a cavity for forming the container: a first set of the inserts for forming a first set of features of the container being formed of a first material and a second set of inserts for forming a second set of features of the container being formed of a second material, the first set of inserts being machined to the required shape for fitting within the carrier units and for forming the first set of features and the second set of inserts being machined so as to fit within the carrier units but one or more of the second set of inserts being formed with excess material on surfaces thereof defining said second set of features pending a decision as to the precise shape of said second set of features, whereby once said decision has been made the tool can be completed by machining said excess material to the required shape and assembling the inserts in the mould.
2. A method as claimed in claim 1 in which one or more of the second set of features is changed by replacing one or more of said second set of inserts by one or more further inserts with the excess material thereon machined to different shape.
3. A method as claimed in claim 1 or 2 in which the second set of features comprise static features on the base, lid or spine portions.
4. A method as claimed in any preceding claim in which the second set of features comprises one or more of the following: specific external features, internal graphic features, and a surround for extending around

the periphery or part of the periphery of information storage media held within the container.


5. A method as claimed in claim 4 in which container is provided with a film or sleeve extending around the exterior thereof for receiving an information sheet, the film or sleeve extending over the majority of external faces of the lid portion, base portion and spine portion apart from a band at one end (or both ends) of the container, said band remaining uncovered by said film or sleeve to provide an area in which said specific external features can be formed.
6. A method as claimed in claim 5 in which said band stands proud of the adjacent areas of the external surfaces of the container area (over which ~~the film or sleeve is provided~~).
7. A method as claimed in any preceding claim in which the container is adapted to hold information storage media in the form of a disk.
8. A method as claimed in claim 7 in which the holding means comprises a hub for releasably engaging the disk via a central aperture therein, the hub being one of said first set of features.
9. A method as claimed in claims 4 and 8 in which the surround comprises a substantially circular or part circular upstand for extending around the periphery of a disk held on said hub.
10. A method as claimed in claim 9 in which the surround has an inner edge adjacent the periphery of the disk which is substantially circular or part circular and an outer edge which is non-circular or partially non-circular.
11. A method as claimed in claim 9 or 10 in which the base portion has a substantially flat, inner surface and said upstand projects from said surface.
12. A method as claimed in claims 4 and 11 in which said inner surface is rectangular, the width (shorter dimension) of the rectangle being of

sufficient size to receive the diameter of said disk and the length (longer dimension) of the rectangle being of sufficient size to receive the diameter of said disk with a space left at one or both ends of the rectangle, said spaces providing an area or areas in which said internal graphics features can be formed.

13. A method as claimed in any preceding claim in which the first material is a hard material whereas the second material is a softer material.
14. A method as claimed in any preceding claim in which the first material is a steel.
15. A method as claimed in any preceding claim in which the second material is a copper alloy.
16. A method as claimed in claim 15 in which, following machining of said excess material, the surfaces of the second set of components defining the shape of the second set of features are provided with a hard coating.
17. A method as claimed in claim 16 in which said coating comprises a nickel or titanium alloy with an additional outer coating of chromium.
18. A method of making an injection moulded container substantially as hereinbefore described with reference to one or more of the accompanying drawings.
19. An injection moulded container formed by a method as claimed in any preceding claim.
20. A plurality of injection moulded containers as claimed in claim 20 each being similar apart from some having a first set of customer specific features and some having a second set of customer specific features (differing from the first set).
21. A mould tool for use in a method as claimed in any of claims 1 to 18.

22. A mould tool as claimed in claim 21 comprising a first set of inserts for forming a first set of features and a plurality of second sets of inserts each second set being for forming a different set of customer specific features.

1/5



2/5




FIG. 2 17B




FIGURE 3A

FIGURE 3B

31

33

32

34

4/5




FIGURE 4

5/5





FIGURE 5